

CUTTING LINES

WITH HARD METAL CIRCULAR BLADE



Model MD70


Model MD100

Model MD150





Horizontal and vertical vice to guarantee a good clamping of the bar



Material feeding controlled by CN, that allows an accurate feeding of the bar. The complete feeding part is walking to avoid signs on the material and bad function stop due to distorted bars

CUTTING LINES models MD70 - MD100 - MD150

MAIN FEATURE

High speed and accuracy cut, with an excellent finishing and a long live of the blade, thank to a new control.

5 times faster than a cut with HSS, proper for many kinds of alloy, aluminium, normal steel, alloy steel, stainless steel.

Thin blade thickness (2 or 2,5 mm) that allows a reduced stress and energy consumption.


The strong and ant vibration design assure a good and fast cut for a long live of the blade.

The microfog Spraimist is standard, for a clean cut and cooling of the pieces .


The machine is complete with sliding guides to avoid blade oscillations. Head movement with hydraulic motor and ball screw.

Easy touch screen to control the lengths and the quantity of the pieces. On the display will appear if there are errors or bad functions of the machine for an simple control of the machine.


Types of loaders for models MD70 - MD100 - MD150



Loader type CS



Loader type CM



Loader type P

**Model
MD 100**



Automatic, high speed
cutting machine for full
material.
With hard metal
circular blade



TECHNICAL DATAS		MD 70	MD 100	MD 150
Cutting capacity	mm	● Ø15~Ø70 - ■ 60	● Ø20~Ø100 - ■ 80	● Ø75~Ø150 - ■ 100
Motor output	Hp	Blade - 7,5	Blade - 11	Blade - 15
Blade size		Ø 280xØ40xT2.0	Ø360x40xT2.5	Ø460xØ50xT2.7
Blade speed - inverter control	rpm	90 → 130	70 → 130	60 → 90
Feeding blade		Hydraulic motor and ball screw - Brushless motor and ball screw (OPTIONAL)		
Feeding bar		Servo motor with ball screw		
Auto feeding length	mm	Single feed 6~600/A multiple feed 600~9999		
Chips conveyor		Chips conveyor (OPTIONAL)		
Cooling systems		Spraimist, compressed air, mixed oil		
Cans capacity	L	120 Pump, cooling 3		
Machine weight	Kg	3100	4000	5200

www.omp-group.it



seller stamp

OMP s.r.l.

**via Delle Prese 42/44
36014 Santorso (VI) - ITALY
tel. +39 0445 640822
fax +39 0445 640225
email: info@omp-group.it**

