



LPC 500-MIRROR “Mirror” polishing machine for straight and bent parts



Technical features:

Min. / max. diameter	20 / 150 mm.
Min. bending radius	190 mm.
Abrasive belts size	1250x80 mm.
Disc motor	1,5 kw.
Abrasive belts motor	5,5 kw.
Waterpump motor	0,2 kw.
Net Weight	390 kg.
Dimensions	130x145xh.190 cm.



Collecting and filtering equipment for the cooling mixture complete with watersprout for cleaning

Description:


Brand new technology: orbital mirror polishing machine with solid paste dispenser for mirror finishing and buffing on straight and bent tubes made of stainless steel, brass, iron, or any other kind of metal having round, oval or irregular section, from 6 to 130 mm..

For some particular applications, through abrasive belts is also suitable for grinding and surfaces preparation for mirror polishing.


Grinding operations can be “DRY” (standard version of machine) or “WET” (by adding an external filtering and cooling tank, with manual /automatic filtering paper roll up).

Standard equipment:

Motors voltage 400V 50Hz; Holding boards for workpieces; Adjustment wrenches; Instruction book; CE conformity certificate;



Round and oval tubes grinding



Square tubes max. 20x20 mm. grinding


Basic machine price:

LPC 300 Mirror Polishing and grinding machine for straight/bent parts	€
Safety devices according to CE rules	€


* Equipment on request: see next page

LPC 400-Mirror: Equipment on request

Pict	Code	Description	X	€	Price
1	39	AN foot pedal equipment for an easier workpiece insert between the abrasive belts		€	
2	-	Automatic dispenser for liquid abrasive paste		€	
3	A33	Dust collection cap (for "dry" processings)		€	
	ADF10	ADN feed system for straight round pipes		€	
4-5	A40	AV SELF-CENTERING feed with adjustable speed by Inverter for straight and taper parts <u>max. diam. 45 mm.</u> (hinged for "manual" feed processings)		€	-
4-5	GEM	Powered outfeed rollers for AV feed		€	-
6	ALT	ALT SELF-CENTERING automatic feed for straight and taper parts <u>max 150 mm. diameter</u> and adjustable feed with inverter (hinged for "manual" feed processings)		€	-
7	A41	AVU "UNIVERSAL" feed for both straight and bent parts with adjustable speed by inverter		€	-
8	11.1	Abrasive belts speed adjustable (10-30 mt./sec.) with increased power special inverter (5,5 kw.) and digital display with mt./sec. real values		€	
9	CPP	CPP "step-by-step" loader-unloader for straight parts having round, oval, elliptical shape with length 1500-6000 mm.		€	
10	AM APM	AM "manual" special feed and APN automatic special feed with "chuck point-tailstock system" for short parts		€	-
	35	BLOC equipment for disc rotation stop		€	-



Pict. 1





Pict. 2


Pict. 2



Pict. 5



Pict. 6



Pict. 7



Pict. 8



Pict. 10

Sales terms:

Teslim zamanı	40 gün
Teslim Yeri	İstanbul Gümrük teslim
Paketleme	Ağaç Palet ile
KDV	-
Ödeme	30% sipariş ile Peşin; 70% İtalya Yükleme öncesi



Tel: 0212 576 25 37
Fax: 0212 549 43 62
www.akesmakina.com